

**WHAT IS CLAIMED IS:**

1. A constituent decoding method for decoding a turbo code, comprising the steps of:

5 (1) calculating the best and second best metrics of metrics being the sums of state metrics and a branch metric for a received information symbol in a turbo decoding trellis at an arbitrary time point during turbo decoding of the information symbol;

(2) calculating the difference between the best metric for the information  
10 symbol being 0 and the best metric for the information symbol being 1;

(3) calculating the difference between the second best metric for the information symbol being 0 and the second best metric for the information symbol being 1;

(4) calculating the difference between the best metric difference and the  
15 second best metric difference and multiplying the calculated difference by a weighting factor, so that the metrics being the sums of the state metrics and the branch metric are linear; and

(5) updating the log likelihood ratio (LLR) of the information symbol using the best metric difference obtained in the step of (2) and the product  
20 obtained in the step of (4) and deciding the value of the information symbol according to the updated LLR.

2. The constituent decoding method of claim 1, further comprising the step of calculating extrinsic information using the updated LLR, an input  
25 symbol reflecting SNR (Signal to Noise Ratio), and the a priori information of the input symbol after the step of (5).

3. The constituent decoding method of claim 1, wherein the weighting factor is determined by

30

$$\text{Weighting factor} = K \cdot W_f$$

.....(13)

where  $W_f$  is less than 1 and close to 1 and  $K$  is the mean inclination of tangent lines of a log function  $l(x) = \log(1 + e^{-x})$ .

5

4. The constituent decoding method of claim 3, wherein  $W_f$  is greater than 0.588235.

5. The constituent decoding method of claim 1, wherein the  
10 weighting factor is derived from a function linearized from a log function using the mean inclination of tangent lines of the log function, the log function being represented by the difference between the best metric and the second best metric.

6. The constituent decoding method of claim 3, wherein the mean  
15 inclination of the tangent lines is an integer between 0 and 9.

7. A constituent decoder for decoding a turbo code, comprising:  
a first adder for calculating the difference between the best metric for a  
received information symbol being 1 and the best metric for the information  
20 symbol being 0 in a turbo decoding trellis at an arbitrary time point during turbo decoding the information symbol;

a second adder for adding the transmission information and a priori  
information of the information symbol;

a third adder for calculating the difference between the outputs of the  
25 first and second adders and outputting the difference as extrinsic information;

a first multiplier for multiplying the output of the third adder by a  
predetermined weighting factor as a feedback gain;

a correction value calculator for calculating a correction value using the  
difference between the best metric and second best metric of the received  
30 information symbol; and

a fourth adder for adding the correction value to the output of the first multiplier.

8. The constituent decoder of claim 7, wherein the correction value  
5 calculator comprises:

a fifth adder for calculating the difference between the best metric and the second best metric for the information symbol being 0;

a sixth adder for calculating the difference between the best metric and the second best metric for the information symbol being 1;

10 a look-up table for storing log function-based correction values for the outputs of the fifth and sixth adders and outputting correction values for the outputs of the fifth and sixth adders;

a seventh adder for calculating the difference between the correction values;

15 a second multiplier for multiplying the output of the seventh adder by a predetermined weighting factor;

an eighth adder for calculating the difference between the outputs of the fifth and sixth adders;

20 a third multiplier for multiplying the output of the eighth adder by the inclination of a linear function approximated from the log function; and

a selector for selecting one of the outputs of the second and third multipliers according to the reliability of the signal to noise ratio (SNR) of the received information symbol.

25 9. The constituent decoder of claim 8, wherein if the weighting factor and the inclination of the linear function can be expressed as 2's exponents, each of the multipliers is implemented as a bit selector.